The Cleaning Resource

SAFETY DATA SHEET

1. Identification

Product identifier 1907 Waterborne Urethane Gym Finish

Other means of identification

577N-178B SDS number **Product code** HIL00280 Recommended use Gym Finish

Recommended restrictions For Labeled Use Only Manufacturer/Importer/Supplier/Distributor information

Manufacturer

HILLYARD INDUSTRIES Company name **Address** 302 North Fourth St. St. Joseph, MO 64501

Contact person Regulatory Affairs

Telephone number (816) 233-1321 (Ext. 8285)

Fax (816) 383-8485

regulatoryaffairs@hillyard.com E-mail

(800) 424-9300 **Emergency telephone #**

(Only in the event of chemical emergency involving a spill, leak, fire, exposure or

accident involving chemicals)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A Reproductive toxicity Category 1B

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word

Hazard statement Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May damage

fertility or the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

> and understood. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye

protection/face protection.

If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable Response

for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. If exposed or concerned: Get medical

advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated

clothing and wash before reuse.

Material name: 1907 Waterborne Urethane Gym Finish

SDS US HIL00280 Version #: 04 Revision date: 04-10-2017 Issue date: 11-20-2014

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law in compliance with applicable federal, state and local requirements. CONTAINER DISPOSAL: Triple rinse (or equivalent), then offer clean, dry container for recycling or reconditioning.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

Use With Adequate Ventilation. Avoid breathing vapors or spray mist. Open windows and doors, use exhaust fans or other means to insure fresh air entry during application and drying. NOTICE: Saw dust from freshly sanded floors or dust from wood floors that have been abraded between coats will spontaneously catch fire if improperly discarded. Immediately after abrading or sanding wood floors, place dust waste in a sealed, water-filled metal container and immediately remove from building.

NOTICE: Rags or applicators soaked in a combustible liquid will spontaneously catch fire if improperly discarded. Immediately after using rags or applicators soaked in a combustible liquid, place waste in a sealed, water-filled metal container and immediately remove from building.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
1-Methyl-2-Pyrrolidinone		872-50-4	3 - < 5
Triethylamine		121-44-8	1 - < 3
Other components below report	table levels		90 - 100

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON Inhalation

CENTER or doctor/physician if you feel unwell.

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get Skin contact

medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Only induce vomiting at the instruction of Ingestion

medical personnel. Never give anything by mouth to an unconscious person.

vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice **General information** (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted. General fire hazards

Material name: 1907 Waterborne Urethane Gym Finish

HIL00280 Version #: 04 Revision date: 04-10-2017 Issue date: 11-20-2014

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Not available.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Triethylamine (CAS 121-44-8)	PEL	100 mg/m3	
		25 ppm	
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	
Triethylamine (CAS 121-44-8)	STEL	1 ppm	
,	TWA	0.5 ppm	
US. AIHA Workplace Environme	ntal Exposure Level (WEEL) Gu	iides	
Components	Туре	Value	
1-Methyl-2-Pyrrolidinone (CAS 872-50-4)	TWA	40 mg/m3	
		10 ppm	

Biological limit values

ACGIH Biological Exposure Indices					
Components	Value	Determinant	Specimen	Sampling Time	
1-Methyl-2-Pyrrolidinone (CAS 872-50-4)	100 mg/l	5-Hydroxy-N-m ethyl-2-pyrrolid one	Urine	*	

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

1-Methyl-2-Pyrrolidinone (CAS 872-50-4)

Can be absorbed through the skin.

Triethylamine (CAS 121-44-8)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Triethylamine (CAS 121-44-8) Can be absorbed through the skin.

US WEEL Guides: Skin designation

1-Methyl-2-Pyrrolidinone (CAS 872-50-4) Can be absorbed through the skin.

HIL00280 Version #: 04 Revision date: 04-10-2017 Issue date: 11-20-2014

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Use safety eyewear with splash guards or side shields, chemical goggles,

or face shields.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other None normally required. If unable to avoid prolonged or repeated contact with skin, wear

impervious clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards None known.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Opaque, off-white liquid

Physical stateLiquid.FormLiquid.ColorOff-white

Odor Non-objectional odor

Odor thresholdNot availablepH7.5 - 8.5Melting point/freezing pointNot available

Initial boiling point and boiling

range

> 212 °F (> 100 °C)

Flash point > 200.0 Tag Closed Cup Evaporation rate < 1 Ethyl ether = 1

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 17.61 mm Hg

Vapor density 0.8653 AIR=1

Relative density 1.0196 at 77°F

Solubility(ies)

Solubility (water) Dispersible

Partition coefficient Not available

(n-octanol/water)

Auto-ignition temperature Not available

Decomposition temperature Not available

Viscosity Not available

Other information

Brookfield viscosity

Density

Explosive properties

Oxidizing properties

Percent volatile

VOC

10 - 30 cP

8.49 lb/gal

Not explosive.

Not oxidizing.

70 - 71 %

< 200 g/l

Material name: 1907 Waterborne Urethane Gym Finish

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eve irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Not known.

Test Results Components **Species**

1-Methyl-2-Pyrrolidinone (CAS 872-50-4)

<u>Acute</u>

Oral

LD50 Rat 3914 mg/kg

Triethylamine (CAS 121-44-8)

Acute Dermal

LD50 Rabbit 416 mg/kg

Inhalation

LC50 Rat 0.42 mg/l, 1 Hours

Oral

LD50 Rat 460 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicity May damage fertility or the unborn child.

Material name: 1907 Waterborne Urethane Gym Finish SDS US HIL00280 Version #: 04 Revision date: 04-10-2017 Issue date: 11-20-2014

^{*} Estimates for product may be based on additional component data not shown.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

Prolonged inhalation may be harmful. **Chronic effects**

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

1-Methyl-2-Pyrrolidinone -0.54 Triethylamine 1.45

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US federal regulations**

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Triethylamine (CAS 121-44-8) Listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

SDS US HIL00280 Version #: 04 Revision date: 04-10-2017 Issue date: 11-20-2014

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1-Methyl-2-Pyrrolidinone	872-50-4	3 - < 5
Triethylamine	121-44-8	1 - < 3

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Triethylamine (CAS 121-44-8)

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Triethylamine (CAS 121-44-8) Other Flavoring Substances with OSHA PEL's

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer and

birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

1-Methyl-2-Pyrrolidinone (CAS 872-50-4) Listed: June 15, 2001

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1-Methyl-2-Pyrrolidinone (CAS 872-50-4)

Triethylamine (CAS 121-44-8)

International Inventories

Country(s) or region Inventory name On inventory (yes/no)* Yes

Canada Domestic Substances List (DSL) United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

11-20-2014 Issue date **Revision date** 04-10-2017

Version # 04

Health: 2* **HMIS®** ratings

Flammability: 0 Physical hazard: 0

Disclaimer No representations or warranties, either express or implied, of merchantability, fitness for a

particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or

disposal of these products.

This document has undergone significant changes and should be reviewed in its entirety. **Revision information**

SDS US HIL00280 Version #: 04 Revision date: 04-10-2017 Issue date: 11-20-2014

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).