

Stargon or Stargon SS

Safety Data Sheet P-4788

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1981 Revision date: 09/30/2014 Supersedes: 12/01/2007

SECTION: 1. Product and company identification

1.1. Product identifier

Product form : Mixture
Formula : Non-oxidizing mixtures of argon, carbon dioxide, and up to 5 percent oxygen (Stargon) or nitrogen (Stargon SS)
Other means of identification : Stargon, Stargon SS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use
Electric Arc Welding

1.3. Details of the supplier of the safety data sheet

Praxair, Inc.
39 Old Ridgebury Road
Danbury, CT 06810-5113 - USA
T 1-800-772-9247 (1-800-PRAXAIR) - F 1-716-879-2146
www.praxair.com

1.4. Emergency telephone number

Emergency number : Onsite Emergencies: 1-800-645-4633
CHEMTREC: USA 1-800-424-9300, International 001-703-527-3887 (Collect calls accepted, contract 17729)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Compressed gas H280

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Warning

Hazard statements (GHS-US)

: H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED
OSHA-H01 - MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.
CGA-HG01 - MAY CAUSE FROSTBITE.
CGA-HG03 - MAY INCREASE RESPIRATION AND HEART RATE.
Precautionary statements (GHS-US) : P202 - Do not handle until all safety precautions have been read and understood
P261 - Avoid breathing gas
P262 - Do not get in eyes, on skin, or on clothing
P271+P403 - Use and store only outdoors or in a well-ventilated place.
CGA-PG05 - Use a back flow preventive device in the piping.
CGA-PG10 - Use only with equipment rated for cylinder pressure.
CGA-PG06 - Close valve after each use and when empty.
CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

Stargon or Stargon SS

Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Argon	(CAS No) 7440-37-1	90 - 99.9998
Carbon dioxide	(CAS No) 124-38-9	<= 10
Oxygen	(CAS No) 7782-44-7	0 - 5
Nitrogen, compressed	(CAS No) 7727-37-9	0 - 5

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- First-aid measures after skin contact : Wash with plenty of soap and water. For exposure, immediately warm frostbite area with warm water not to exceed 105°F (41°C). Water temperature should be tolerable to normal skin. Maintain skin warming for at least 15 minutes or until normal coloring and sensation have returned to the affected area. In case of massive exposure, remove clothing while showering with warm water. Seek medical evaluation and treatment as soon as possible.
- First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Get immediate medical attention.
- First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

5.2. Special hazards arising from the substance or mixture

- Reactivity : No reactivity hazard other than the effects described in sub-sections below.

5.3. Advice for firefighters

- Firefighting instructions : Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart L—Fire Protection.
- Protection during firefighting : Compressed gas: asphyxiant. Suffocation hazard by lack of oxygen.
- Special protective equipment for fire fighters : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
- Specific methods : Stop flow of product if safe to do so. Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. Use water spray or fog to knock down fire fumes if possible.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate area. Ensure adequate air ventilation. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Stop leak if safe to do so.

Stargon or Stargon SS

Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Argon (7440-37-1)		
ACGIH	Not established	
USA OSHA	Not established	
Carbon dioxide (124-38-9)		
ACGIH	ACGIH TLV-TWA (ppm)	5000 ppm
ACGIH	ACGIH TLV-STEL (ppm)	30000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	9000 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm
ACGIH	Not established	

Stargon or Stargon SS

Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Carbon dioxide (124-38-9)

USA OSHA	Not established
----------	-----------------

Oxygen (7782-44-7)

ACGIH	Not established
USA OSHA	Not established

Nitrogen, compressed (7727-37-9)

ACGIH	Not established
USA OSHA	Not established

8.2. Exposure controls

Appropriate engineering controls	: Oxygen detectors should be used when asphyxiating gases may be released. Systems under pressure should be regularly checked for leakages. Provide adequate general and local exhaust ventilation. Consider work permit system e.g. for maintenance activities.
Hand protection	: Wear working gloves when handling gas containers.
Eye protection	: Wear safety glasses with side shields.
Respiratory protection	: When workplace conditions warrant respirator use, follow a respiratory protection program that meets OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable). Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure (e.g., an organic vapor cartridge). For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).
Thermal hazard protection	: None necessary.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
Other information	: Wear safety shoes while handling containers.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Color	: Colorless
Odor	: Odorless.
Odor threshold	: No data available
pH	: Not applicable.
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: Not applicable.
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: Not applicable.
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 1.68 kg/m ³
Relative gas density	: 1.4
Solubility	: Water: No data available
Log Pow	: Not applicable.

Stargon or Stargon SS

Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Log Kow	: Not applicable.
Viscosity, kinematic	: Not applicable.
Viscosity, dynamic	: Not applicable.
Explosive properties	: Not applicable.
Oxidizing properties	: None.
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Alkali metals, Alkaline earth metals, Acetylide forming metals, Chromium, Titanium > 1022°F (550°C), Uranium (U) > 1382°F (750°C), Magnesium > 1427°F (775°C).

10.6. Hazardous decomposition products

Using this product in welding and cutting may create additional hazards. The arc from electric arc welding may form gaseous reaction products such as carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc. Other decomposition products of arc welding and cutting originate from the volatilization, reaction, and oxidization of the material being worked.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified pH: Not applicable.
Serious eye damage/irritation	: Not classified pH: Not applicable.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified No known effects from this product.
Aspiration hazard	: Not classified Not applicable.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: No ecological damage caused by this product.
-------------------	--

Stargon or Stargon SS

Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

12.2. Persistence and degradability

Stargon, Stargon SS

Persistence and degradability	No ecological damage caused by this product.
-------------------------------	--

Argon (7440-37-1)

Persistence and degradability	No ecological damage caused by this product.
-------------------------------	--

Carbon dioxide (124-38-9)

Persistence and degradability	No ecological damage caused by this product.
-------------------------------	--

Oxygen (7782-44-7)

Persistence and degradability	No ecological damage caused by this product.
-------------------------------	--

Nitrogen, compressed (7727-37-9)

Persistence and degradability	No ecological damage caused by this product.
-------------------------------	--

12.3. Bioaccumulative potential

Stargon, Stargon SS

Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.

Argon (7440-37-1)

Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.

Carbon dioxide (124-38-9)

BCF fish 1	(no bioaccumulation)
Log Pow	0.83
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.

Oxygen (7782-44-7)

Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.

Nitrogen, compressed (7727-37-9)

Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.

12.4. Mobility in soil

Stargon, Stargon SS

Mobility in soil	No data available.
------------------	--------------------

Argon (7440-37-1)

Mobility in soil	No data available.
Ecology - soil	No ecological damage caused by this product.

Carbon dioxide (124-38-9)

Mobility in soil	No data available.
Ecology - soil	No ecological damage caused by this product.

Oxygen (7782-44-7)

Mobility in soil	No data available.
Ecology - soil	No ecological damage caused by this product.

Nitrogen, compressed (7727-37-9)

Mobility in soil	No data available.
------------------	--------------------

Stargon or Stargon SS

Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Nitrogen, compressed (7727-37-9)

Ecology - soil	No ecological damage caused by this product.
----------------	--

12.5. Other adverse effects

Effect on ozone layer	: None.
Effect on the global warming	: Contains greenhouse gas(es) not covered by 842/2006/EC.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: May be vented to atmosphere in a well ventilated place. Consult supplier for specific recommendations. Do not discharge into any place where its accumulation could be dangerous. Contact supplier if guidance is required.
Waste disposal recommendations	: Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

SECTION 14: Transport information

In accordance with DOT	
Transport document description	: UN1956 Compressed gas, n.o.s. (Argon ; Carbon dioxide), 2.2
UN-No.(DOT)	: UN1956
Proper Shipping Name (DOT)	: Compressed gas, n.o.s. (Argon ; Carbon dioxide)
Department of Transportation (DOT) Hazard Classes	: 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115
Hazard labels (DOT)	: 2.2 - Non-flammable gas



DOT Symbols	: G - Identifies proper shipping name (PSN) requiring the addition of technical name(s) in parentheses following the PSN.
-------------	---

Additional information

Other information	: No supplementary information available.
Special transport precautions	: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

ADR

Transport document description	: UN 1956 COMPRESSED GAS, N.O.S., 2.2, (E)
Class (ADR)	: 2 - Gases
Hazard identification number (Kemler No.)	: 20
Classification code (ADR)	: 1A
Hazard Class Labels (ADR)	: 2.2 - Non-flammable compressed gas



Stargon or Stargon SS

Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Orange plates

:



Tunnel restriction code (ADR)

: E

Transport by sea

UN-No. (IMDG)

: 1956

Proper Shipping Name (IMDG)

: COMPRESSED GAS, N.O.S.

Class (IMDG)

: 2 - Gases

Air transport

UN-No.(IATA)

: 1956

Proper Shipping Name (IATA)

: COMPRESSED GAS, N.O.S.

Class (IATA)

: 2

SECTION 15: Regulatory information

15.1. US Federal regulations

Stargon, Stargon SS

SARA Section 311/312 Hazard Classes

Sudden release of pressure hazard
Immediate (acute) health hazard

All components of this product are listed on the Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Argon (7440-37-1)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class A - Compressed Gas

Carbon dioxide (124-38-9)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class A - Compressed Gas

Oxygen (7782-44-7)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class A - Compressed Gas
Class C - Oxidizing Material

Nitrogen, compressed (7727-37-9)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class A - Compressed Gas

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Ox. Gas 1 H270

Compressed gas H280

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

No additional information available

15.3. US State regulations

Stargon or Stargon SS

Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

Argon (7440-37-1)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Carbon dioxide (124-38-9)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Oxygen (7782-44-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Nitrogen, compressed (7727-37-9)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 9/30/2014 12:00:00 AM

Stargon or Stargon SS

Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Fumes and gases produced during welding and cutting processes can be dangerous to your health and may cause serious lung disease. KEEP YOUR HEAD OUT OF FUMES. DO NOT BREATHE FUMES AND GASES. Use enough ventilation, local exhaust, or both to keep fumes and gases from your breathing zone and the general area. Short-term overexposure to fumes may cause dizziness, nausea, and dryness or irritation of the nose, throat, and eyes; or may cause other similar discomfort. Contaminants in the air may add to the hazard of fumes and gases. One such contaminant, chlorinated hydrocarbon vapors from cleaning and degreasing activities, poses a special risk. DO NOT USE ELECTRIC ARCS IN THE PRESENCE OF CHLORINATED HYDROCARBON VAPORS—HIGHLY TOXIC PHOSGENE MAY BE PRODUCED. Metal coatings such as paint, plating, or galvanizing may generate harmful fumes when heated. Residues from cleaning materials may also be harmful. AVOID ARC OPERATIONS ON PARTS WITH PHOSPHATE RESIDUES (ANTI-RUST, CLEANING PREPARATIONS)—HIGHLY TOXIC PHOSPHINE MAY BE PRODUCED.

Praxair asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair SDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Praxair sales representative, local distributor, or supplier, or download from www.praxair.com. If you have questions regarding Praxair SDSs, would like the document number and date of the latest SDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (Phone: 1-800-PRAXAIR/1-800-772-9247; Address: Praxair Call Center, Praxair, Inc., P.O. Box 44, Tonawanda, NY 14151-0044).

PRAXAIR and the Flowing Airstream design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.

Full text of H-phrases: see section 16:

Compressed gas	Gases under pressure Compressed gas
Ox. Gas 1	Oxidizing gases Category 1
H270	MAY CAUSE OR INTENSIFY FIRE; OXIDIZER
H280	CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

NFPA health hazard


: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard

: 0 - Materials that will not burn.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

: 0 Minimal Hazard - No significant risk to health

Flammability

: 0 Minimal Hazard

Physical

: 3 Serious Hazard

SDS US (GHS HazCom 2012) - Praxair

Stargon or Stargon SS

Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.